


General Description:

GL44N25A8, the silicon N-channel Enhanced VDMOSFET, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-220AB, which accords with the RoHS standard.

V_{DSS}	250	V
I_D	44	A
$P_D(T_C=25^{\circ}C)$	307	W
$R_{DS(ON).TYP.}$	58	m Ω


Features:

- Fast Switching
- Low ON Resistance
- Low Gate Charge
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test



Applications:

- Power switch circuit of adaptor and charger



Absolute (Tc=25°C unless otherwise specified):

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	250	V
I_D	Continuous Drain Current	44	A
	Continuous Drain Current $T_C=100^{\circ}C$	26.4	A
I_{DM}^{a1}	Pulsed Drain Current	176	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}^{a2}	Single Pulse Avalanche Energy	2050	mJ
E_{Ar}^{a1}	Avalanche Energy ,Repetitive	30.8	mJ
I_{AR}^{a1}	Avalanche Current	44	A
dv/dt^{a3}	Peak Diode Recovery dv/dt	5.0	V/ns
P_D	Power Dissipation	307	W
	Derating Factor above 25°C	2.46	W/°C
T_J, T_{stg}	Operating Junction and Storage Temperature Range	150, -55 to 150	°C
T_L	Maximum Temperature for Soldering	300	°C

Caution Stresses greater than those in the "Absolute Maximum Ratings" may cause permanent damage to the device



GL44N25A8

Silicon N-Channel Power MOSFET

Thermal Characteristics

Symbol	Parameter	Rating	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.35	°C/ W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	62.5	°C/ W

Electrical Characteristics (Tc= 25°C unless otherwise specified):

OFF Characteristics

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
V_{DSS}	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	250	--	--	V
$\Delta BV_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	$I_D=250\mu A$, Reference 25°C	--	0.2	--	V/°C
I_{DSS}	Drain to Source Leakage Current	$V_{DS}=250V, V_{GS}=0V, T_a=25^\circ C$	--	--	1	μA
		$V_{DS}=200V, V_{GS}=0V, T_a=125^\circ C$	--	--	10	
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+30V$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-30V$	--	--	-100	nA

ON Characteristics

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10V, I_D=22A$	--	58	69	mΩ
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	--	4.0	V
g_{fs}	Forward Trans conductance	$V_{DS}=15V, I_D=22A$	--	30	--	S
Pulse width < 380μs; duty cycle < 2%.						

Dynamic Characteristics

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
C_{iss}	Input Capacitance	$V_{GS}=0V, V_{DS}=25V$ $f=1.0MHz$	--	3100	--	pF
C_{oss}	Output Capacitance		--	320	--	
C_{rss}	Reverse Transfer Capacitance		--	45	--	

Resistive Switching Characteristics

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D=44A, V_{DD}=125V$ $V_{GS}=10V, R_g=12\Omega$	--	35	--	ns
t_r	Rise Time		--	82	--	
$t_{d(OFF)}$	Turn-Off Delay Time		--	180	--	
t_f	Fall Time		--	90	--	
Q_g	Total Gate Charge	$I_D=44A, V_{DD}=125V$ $V_{GS}=10V$	--	65	--	nC
Q_{gs}	Gate to Source Charge		--	15	--	
Q_{gd}	Gate to Drain ("Miller") Charge		--	35	--	



GL44N25A8

Silicon N-Channel Power MOSFET

Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I_{SD}	Continuous Source Current (Body Diode)		--	--	44	A
I_{SM}	Maximum Pulsed Current (Body Diode)		--	--	176	A
V_{SD}	Diode Forward Voltage	$I_S=44A, V_{GS}=0V$	--	--	1.5	V
t_{rr}	Reverse Recovery Time	$I_S=44A, T_J=25^{\circ}C$	--	400	--	ns
Q_{rr}	Reverse Recovery Charge	$di_F/dt=100A/\mu s, V_{GS}=0V$	--	3.4	--	μC

a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: $L=10mH, I_D=20.2A$, Start $T_J=25^{\circ}C$

a3: $I_{SD}=44A, di/dt \leq 200A/\mu s, V_{DD} \leq BV_{DS}$, Start $T_J=25^{\circ}C$

Characteristics Curve:

Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On-Resistance Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature




Figure 11. Transient Thermal Response Curve

