

General Description

GL24N100A47, the silicon N-channel Enhanced VDMOSFET, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-247, which accords with the RoHS standard.



$V_{DSS}(T_C=150^{\circ}\text{C})$	1000	V
I_D	24	A
$P_D(T_C=25^{\circ}\text{C})$	500	W
$R_{DS(ON)MAX}$	450	mΩ

Features

- Fast Switching
- ESD Improved Capability
- Low Gate Charge
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test

Applications

- Power switch circuit of PC POWER



Absolute (Tc=25°C unless otherwise specified)

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	1000	V
I_D	Continuous Drain Current	24	A
	Continuous Drain Current $T_C=100^{\circ}\text{C}$	20	A
I_{DM}^{a1}	Pulsed Drain Current (Pulse Width Limited by T_{JM})	60	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}	Single Pulse Avalanche Energy	3	J
E_{Ar}^{a1}	Avalanche Energy ,Repetitive	200	mJ
I_{AR}^{a1}	Avalanche Current	24	A
dv/dt^{a2}	Peak Diode Recovery dv/dt	5.0	V/ns
P_D	Power Dissipation	600	W
	Derating Factor above 25°C	4.8	W/ $^{\circ}\text{C}$
T_J, T_{stg}	Operating Junction and Storage Temperature Range	150, -55 to 150	$^{\circ}\text{C}$
T_L	Maximum Temperature for Soldering	300	$^{\circ}\text{C}$

Caution Stresses greater than those in the "Absolute Maximum Ratings" may cause permanent damage to the device



GL24N100A47

Silicon N-Channel Power MOSFET

Thermal Characteristics

Symbol	Parameter	Rating	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.21	$^{\circ}\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	40	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics (Tc=25°C unless otherwise specified)

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
V_{DS}	Drain to Source Breakdown Voltage	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	1000	--	--	V
I_{DSS}	Drain to Source Leakage Current	$V_{DS}=1000\text{V}, V_{GS}=0\text{V}, T_a=25^{\circ}\text{C}$	--	--	10	μA
		$V_{DS}=800\text{V}, V_{GS}=0\text{V}, T_a=125^{\circ}\text{C}$	--	--	1000	
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+30\text{V}$	--	--	200	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-30\text{V}$	--	--	-200	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10\text{V}, I_D=12\text{A}$	--	--	450	m Ω
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2.5	--	4.5	V
g_{fs}	Forward Trans conductance	$V_{DS}=20\text{V}, I_D=12\text{A}$	--	24	--	S
Pulse width<380 μs ; duty cycle<2%.						

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=25\text{V}$ $f=1.0\text{MHz}$	--	7600	--	pF
C_{oss}	Output Capacitance		--	760	--	
C_{rss}	Reverse Transfer Capacitance		--	88	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D=12\text{A}, V_{DD}=500\text{V}$ $V_{GS}=10\text{V}, R_g=25\Omega$	--	66	--	ns
t_r	Rise Time		--	48	--	
$t_{d(OFF)}$	Turn-Off Delay Time		--	80	--	
t_f	Fall Time		--	50	--	
Q_g	Total Gate Charge	$I_D=12\text{A}, V_{DD}=500\text{V}$ $V_{GS}=10\text{V}$	--	193	--	nC
Q_{gs}	Gate to Source Charge		--	37	--	
Q_{gd}	Gate to Drain ("Miller")Charge		--	70	--	



GL24N100A47

Silicon N-Channel Power MOSFET

Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I_{SD}	Continuous Source Current (Body Diode)		--	--	24	A
I_{SM}	Maximum Pulsed Current (Body Diode)		--	--	96	A
V_{SD}	Diode Forward Voltage	$I_S=24A, V_{GS}=0V$	--	--	1.5	V
t_{rr}	Reverse Recovery Time	$I_S=24A, T_J=25^{\circ}C$	--	550	--	ns
Q_{rr}	Reverse Recovery Charge	$di_F/dt=100A/\mu s, V_{GS}=0V$	--	5.0	--	uC

a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: $I_{SD}=24A, di/dt \leq 100A/\mu s, V_{DD} \leq BV_{DS}$, Start $T_J=25^{\circ}C$



GL24N100A47

Silicon N-Channel Power MOSFET

Characteristics Curves

Fig. 1. Output Characteristics @ $T_J = 25^\circ\text{C}$




Fig. 2. Extended Output Characteristics @ $T_J = 25^\circ\text{C}$




Fig. 3. Output Characteristics @ $T_J = 125^\circ\text{C}$




Fig. 4. $R_{DS(on)}$ Normalized to $I_D = 12A$ Value vs. Junction Temperature




Fig. 5. $R_{DS(on)}$ Normalized to $I_D = 12A$ Value vs. Drain Current





Fig. 6. Maximum Drain Current vs. Case Temperature





GL24N100A47

Silicon N-Channel Power MOSFET

Fig. 7. Input Admittance




Fig. 8. Transconductance




Fig. 9. Forward Voltage Drop of Intrinsic Diode




Fig. 10. Gate Charge




Fig. 11. Capacitance





Fig. 12. Forward-Bias Safe Operating Area





GL24N100A47

Silicon N-Channel Power MOSFET

Fig. 13. Maximum Transient Thermal Impedance

